

K-SVKM NW 7,2 DREH MS-NI

Quick disconnect couplings DN 7.2, nickel-plated brass, swivel type

HANSA FLEX

属性

工作压力	0 - 35 bar, maximum static working pressure (non-pulsating)
空气流量	1.000 l/min (at 6 bar and $\Delta p = 0.5$ bar)
介质温度	0 °C to +70 °C
壳体, 套管	Nickel-plated brass
阀	Brass with a bare metal surface
弹簧、涨圈	Stainless steel 1.4310
锁销	Stainless steel 1.4034
密封材料	NBR



提示

其它数据应客户要求提供。

描述

Universal, one-hand quick disconnect couplings, one side sealing, suitable for a wide range of tasks and applications! The closed sleeve protects the coupling from dirt. In combination with steel plugs, this coupling can also be used for pneumatic tools thanks to its hardened locking pins.

货品

名称	接口	长度 (mm)
K- 07 35 07 28	Stem 6 mm, swivel type	74,0
K- 07 35 07 29	Stem 8 mm, swivel type	74,0
K- 07 35 07 30	Stem 9 mm, swivel type	74,0
K- 07 35 07 31	Stem, 10 mm, swivel type	74,0
K- 07 35 07 32	Stem, 13 mm, swivel type	74,0

附加元件

K-NIPP KUPPL NW7 SCHL MS NI K	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose with swivel nut and kink protector spring
K-NIPPEL KUPPL NW7 AG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, male
K-NIPPEL KUPPL NW7 IG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, female
K-NIPPEL KUPPL NW7 SCHL MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose
K-TUE 7,2 7,8 MS NI	Stems for couplings DN 7.2 - DN 7.8, nickel-plated brass