

# K-SVKM NW 5 IG MS BL1

Quick disconnect couplings DN 5, brass with a bare metal surface, female

**HANSA FLEX**

## 属性

|          |   |
|----------|---|
| 工作压力     | 0 - 35 bar, maximum static working pressure (non-pulsating) |
| 空气流量     | 560 l/min (at 6 bar and $\Delta p = 0.5$ bar)               |
| 介质温度     | -20 °C to +100 °C   |
| 壳体,套管,阀体 | Brass   |
| 弹簧,涨圈,球体 | Stainless steel   |
| 密封材料     | NBR   |



## 提示

其它数据应客户要求提供。

## 描述

One-hand quick disconnect couplings, one side sealing, compact with a large bore and only a small pressure drop. Ideal for: Pneumatic tools, pneumatic applications, medical equipment, instrumentation and control, laboratory, chemical applications, analysis, metering techniques.

## 货品

| 名称             | 接口           | 长度<br>(mm) | SW<br>(mm) |
|----------------|--------------|------------|------------|
| K- 07 35 06 37 | G 1/8 female | 38,0       | 14         |
| K- 07 35 06 38 | G 1/4 female | 38,0       | 17         |
| K- 07 35 06 39 | G 3/8 female | 40,0       | 19         |