

# K-SVKM NW 5 SCHL TUE MS NI

Quick disconnect couplings DN 5, nickel-plated brass with hose stem

**HANSA FLEX**

## 属性

|          |   |
|----------|---|
| 工作压力     | 0 - 35 bar, maximum static working pressure (non-pulsating) |
| 空气流量     | 560 l/min (at 6 bar and $\Delta p = 0.5$ bar)               |
| 介质温度     | -20 °C to +100 °C   |
| 壳体,套管,阀体 | Nickel-plated brass   |
| 弹簧,涨圈,球体 | Stainless steel   |
| 密封材料     | NBR   |



## 提示

其它数据应客户要求提供。

## 描述

One-hand quick disconnect couplings, one side sealing, compact with a large bore and only a small pressure drop. Ideal for: Pneumatic tools, pneumatic applications, medical equipment, instrumentation and control, laboratory, chemical applications, analysis, metering techniques.

## 货品

| 名称             | 接口           | 长度<br>(mm) |
|----------------|--------------|------------|
| K- 07 35 06 62 | Stem, I.D. 4 | 47,0       |
| K- 07 35 06 71 | Stem, I.D. 5 | 46,0       |
| K- 07 35 06 64 | Stem, I.D. 6 | 46,0       |
| K- 07 35 06 72 | Stem, I.D. 8 | 46,0       |
| K- 07 35 06 63 | Stem, I.D. 9 | 46,0       |