

K-SVKM NW 7,8 AG H

Quick disconnect couplings DN 7.8 - for extremely high flow rates, male

HANSA FLEX

属性

| | |
|----------|---------------------------------------|
| 工作压力 | 0 - 35 bar |
| 空气流量 | 2.100 l/min (at $\Delta p = 0.5$ bar) |
| 介质温度 | -20 °C to +40 °C |
| 螺纹件 | Nickel-plated brass |
| 阀体 | Steel, QPQ treated |
| 解锁套管 | Extremely robust, ergonomic plastic |
| 阀,座 | Brass |
| 适用介质 | Only for clean compressed air |
| 密封 | NBR |
| 弹簧,涨圈,球体 | stain less steel |



提示

其它数据应客户要求提供。

描述

One-hand quick disconnect couplings, one side sealing, that combine high flow rates (approx. twice as high as the popular DN 7.2 standard coupling) with minimal coupling forces. Suitable for all applications with an above-average air requirement!

货品

| 名称 | 接口 | 长度 (mm) | SW (mm) |
|----------------|------------|------------|------------|
| K- 07 35 08 47 | G 1/4 male | 65,0 | 19 |
| K- 07 35 08 48 | G 3/8 male | 65,0 | 19 |
| K- 07 35 08 49 | G 1/2 male | 59,0 | 22 |

附加元件

| | |
|-------------------------------|--|
| K-NIPP KUPPL NW7 SCHL MS NI K | Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose with swivel nut and kink protector spring |
| K-NIPPEL KUPPL NW7 AG MS NI | Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, male |
| K-NIPPEL KUPPL NW7 IG MS NI | Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, female |
| K-NIPPEL KUPPL NW7 SCHL MS NI | Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose |
| K-TUE 7,2 7,8 MS NI | Stems for couplings DN 7.2 - DN 7.8, nickel-plated brass |