


K-SVKM NW 7,2 ABSP TUE MS

Quick disconnect couplings DN 7.2, both sides sealing, brass, with hose stem

HANSA FLEX

属性

| | |
|----------|---|
| 工作压力 | 0 - 35 bar, maximum static working pressure (non-pulsating) |
| 空气流量 | 700 l/min (at 6 bar and $\Delta p = 0.5$ bar) |
| 介质温度 | -20 °C to +100 °C |
| 壳体,套管,阀体 | Brass |
| 弹簧,涨圈,球体 | Stainless steel |
| 密封材料 | NBR |



提示

其它数据应客户要求提供。

描述

Couplings, stems and plugs are fitted with a valve. Connection: Both valves open and the medium is allowed to pass. Disconnection: Both valves close and the medium is prevented from escaping.

货品

| 名称 | 接口 | 长度 (mm) | SW (mm) |
|----------------|---------------|------------|------------|
| K- 07 35 07 56 | Stem, I.D. 6 | 58,0 | 21 |
| K- 07 35 12 72 | Stem, I.D. 8 | 58,0 | 21 |
| K- 07 35 07 57 | Stem, I.D. 9 | 58,0 | 21 |
| K- 07 35 12 74 | Stem, I.D. 10 | 58,0 | 21 |
| K- 07 35 07 58 | Stem, I.D. 13 | 58,0 | 21 |