


# K-KOMP ZYL DOPPELW IG

Compact cylinders, double-acting (with magnet), non-cushioned, female piston rod

**HANSA FLEX**

## 属性

适用介质	Filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.
工作压力	Max. 10 bar
起动压力	0,6 bar (Ø 20 bis Ø 32), 0,4 bar (Ø 40 bis Ø 100)
温度范围	-10 °C to +60 °C (Ø 20 to Ø 63) -10 °C to +80 °C (Ø 80 bis Ø 100)
活塞杆	C45 steel, hard chrome-plated
管	Anodised aluminium jacket with T-slots
活塞	POM (Ø 20 to Ø 63); Aluminium (Ø 80 to Ø 100)
密封材料	NBR



## 提示

其它数据应客户要求提供。

## 描述

New series acc. to ISO 21287 characterised by a very short and compact design. The standard type features a magnetic piston. Piston rod optionally with male or female thread.

## 货品

名称	活塞直径 Ø	行程 (mm)	接口	活塞杆内螺纹
K- 07 15 08 87	20 mm	5	M 5	M 6
K- 07 15 08 88	20 mm	10	M 5	M 6
K- 07 15 08 89	20 mm	15	M 5	M 6
K- 07 15 08 90	20 mm	20	M 5	M 6
K- 07 15 08 91	20 mm	25	M 5	M 6
K- 07 15 08 92	20 mm	30	M 5	M 6
K- 07 15 08 93	20 mm	40	M 5	M 6
K- 07 15 08 94	20 mm	50	M 5	M 6
K- 07 15 08 95	20 mm	60	M 5	M 6
K- 07 15 08 96	25 mm	5	M 5	M 6
K- 07 15 08 97	25 mm	10	M 5	M 6
K- 07 15 08 98	25 mm	15	M 5	M 6
K- 07 15 08 99	25 mm	20	M 5	M 6
K- 07 15 09 00	25 mm	25	M 5	M 6
K- 07 15 09 01	25 mm	30	M 5	M 6
K- 07 15 09 02	25 mm	40	M 5	M 6
K- 07 15 09 03	25 mm	50	M 5	M 6
K- 07 15 09 04	25 mm	60	M 5	M 6
K- 07 15 09 05	32 mm	5	G 1/8	M 8
K- 07 15 09 06	32 mm	10	G 1/8	M 8
K- 07 15 09 07	32 mm	15	G 1/8	M 8
K- 07 15 09 08	32 mm	20	G 1/8	M 8
K- 07 15 09 09	32 mm	25	G 1/8	M 8
K- 07 15 09 10	32 mm	30	G 1/8	M 8
K- 07 15 09 11	32 mm	40	G 1/8	M 8
K- 07 15 09 12	32 mm	50	G 1/8	M 8
K- 07 15 09 13	32 mm	60	G 1/8	M 8
K- 07 15 09 14	32 mm	80	G 1/8	M 8
K- 07 15 09 15	40 mm	5	G 1/8	M 8
K- 07 15 09 16	40 mm	10	G 1/8	M 8
K- 07 15 09 17	40 mm	15	G 1/8	M 8
K- 07 15 09 18	40 mm	20	G 1/8	M 8
K- 07 15 09 19	40 mm	25	G 1/8	M 8
K- 07 15 09 20	40 mm	30	G 1/8	M 8
K- 07 15 09 21	40 mm	40	G 1/8	M 8
K- 07 15 09 22	40 mm	50	G 1/8	M 8
K- 07 15 09 23	40 mm	60	G 1/8	M 8
K- 07 15 09 24	40 mm	80	G 1/8	M 8
K- 07 15 09 25	50 mm	5	G 1/8	M 10



尽管经过了仔细审阅,但我们无法完全排除发生错误的可能,对所提供的信息数据本公司不承担任何责任。

09.07.2026

HANSA-FLEX AG

www.hansa-flex.com

1

# K-KOMP ZYL DOPPELW IG

Compact cylinders, double-acting (with magnet), non-cushioned,  
female piston rod



## 货品

名称	活塞直径 Ø	行程 (mm)	接口	活塞杆内螺纹
K-07 15 09 26	50 mm	10	G 1/8	M 10
K-07 15 09 27	50 mm	15	G 1/8	M 10
K-07 15 09 28	50 mm	20	G 1/8	M 10
K-07 15 09 29	50 mm	25	G 1/8	M 10
K-07 15 09 30	50 mm	30	G 1/8	M 10
K-07 15 09 31	50 mm	40	G 1/8	M 10
K-07 15 09 32	50 mm	50	G 1/8	M 10
K-07 15 09 33	50 mm	60	G 1/8	M 10
K-07 15 09 34	50 mm	80	G 1/8	M 10
K-07 15 09 35	63 mm	5	G 1/8	M 10
K-07 15 09 36	63 mm	10	G 1/8	M 10
K-07 15 09 37	63 mm	15	G 1/8	M 10
K-07 15 09 38	63 mm	20	G 1/8	M 10
K-07 15 09 39	63 mm	25	G 1/8	M 10
K-07 15 09 40	63 mm	30	G 1/8	M 10
K-07 15 09 41	63 mm	40	G 1/8	M 10
K-07 15 09 42	63 mm	50	G 1/8	M 10
K-07 15 09 43	63 mm	60	G 1/8	M 10
K-07 15 09 44	63 mm	80	G 1/8	M 10
K-07 15 09 45	80 mm	5	G 1/8	M 12
K-07 15 09 46	80 mm	10	G 1/8	M 12
K-07 15 09 47	80 mm	15	G 1/8	M 12
K-07 15 09 48	80 mm	20	G 1/8	M 12
K-07 15 09 49	80 mm	25	G 1/8	M 12
K-07 15 09 50	80 mm	30	G 1/8	M 12
K-07 15 09 51	80 mm	40	G 1/8	M 12
K-07 15 09 52	80 mm	50	G 1/8	M 12
K-07 15 09 53	80 mm	60	G 1/8	M 12
K-07 15 09 54	80 mm	80	G 1/8	M 12
K-07 15 08 77	100 mm	5	G 1/8	M 12
K-07 15 08 78	100 mm	10	G 1/8	M 12
K-07 15 08 79	100 mm	15	G 1/8	M 12
K-07 15 08 80	100 mm	20	G 1/8	M 12
K-07 15 08 81	100 mm	25	G 1/8	M 12
K-07 15 08 82	100 mm	30	G 1/8	M 12
K-07 15 08 83	100 mm	40	G 1/8	M 12
K-07 15 08 84	100 mm	50	G 1/8	M 12
K-07 15 08 85	100 mm	60	G 1/8	M 12
K-07 15 08 86	100 mm	80	G 1/8	M 12