
K-WTEH SERIE ONE O DRS

Service units, »ONE« Series, without pressure switch



| 属性 | | | | |
|-------------|-----------------------------------|--|--|--|
| 入口压力 | Max. 10 bar | | | |
| 温度范围 | -10 °C to +50 °C | | | |
| 适用介质 | 压缩空气 | | | |
| 保护等级 | IP 65 | | | |
| 工作压力 | 0.5 - 8 bar | | | |
| 压力开关 | Changeover contact | | | |
| 过滤器元件中的气孔宽度 | 20 μm | | | |
| 流量值测量 | At 6,3 bar and $\Delta p = 1$ bar | | | |





提示

其它数据应客户要求提供。

描述

Multifunctional service unit with 6 or 7 functions in a single device: 3/2-way valve (manually operated), filter with automatic drain valve, air ports, pressure regulator, pressure gauge, soft start valve and optional: pressure switch. This combination of extremely good flow rates and a wide range of functions integrated in a single, compact unit saves valuable space and is unmatched by any similar product available in the market! Soft starting independently of the load and easy replacement of the filter cartridge under pressure are just two of the other outstanding features of this amazing device.

订购指南

This unit can also be supplied with many other combinations of functions and port sizes. We will be pleased to make you an offer to match your individual specification on request!

货品

| M HH | | | | | | |
|----------------|--------|---------|-------|----------|------|--|
| 名称 | 接口 | 流量 | Α | В | С | 电压 |
| | | (L/min) | (mm) | | (mm) | |
| K- 07 25 13 79 | G 1/4 | 2400 | 165,5 | 144,0 mm | 35,0 | 24 V DC (for valves and pressure switch) |
| K- 07 25 13 80 | G 3/8 | 3300 | 165,5 | 144,0 mm | 35,0 | 24 V DC (for valves and pressure switch) |
| K- 07 25 13 81 | G 1/2" | 4000 | 165,5 | 144,0 mm | 35,0 | 24 V DC (for valves and pressure switch) |