


K-STECKVERBINDU ST RED 2

Reducers with push-in plug

HANSA FLEX

属性

| | |
|------|------------------|
| 工作压力 | Max. 16 bar |
| 工作温度 | -20 °C to +80 °C |
| 原料 | 黄铜镀镍 |
| 紧压环 | Hostaform |
| 张紧环 | Stainless steel |



提示

其它数据应客户要求提供。

描述

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series: Much easier connection and disconnection of the hose, even with repeated mounting, can also be used for non-calibrated hoses, suitable for vacuum operation.

货品

| 名称 | 用于软管外径-Ø | L1 (mm) | 插式内接头 (mm) |
|----------------|----------|------------|---------------|
| K- 07 40 26 16 | 3 mm | 26,0 | 4 |
| K- 07 40 26 17 | 4 mm | 29,9 | 6 |
| K- 07 40 26 18 | 5 mm | 36,0 | 6 |
| K- 07 40 26 19 | 4 mm | 28,7 | 8 |
| K- 07 40 26 20 | 5 mm | 34,5 | 8 |
| K- 07 40 26 21 | 6 mm | 31,9 | 8 |
| K- 07 40 26 22 | 6 mm | 36,2 | 10 |
| K- 07 40 26 23 | 8 mm | 40,8 | 10 |
| K- 07 40 26 24 | 8 mm | 40,1 | 12 |
| K- 07 40 26 25 | 10 mm | 44,3 | 12 |
| K- 07 40 26 26 | 10 mm | 44,3 | 14 |
| K- 07 40 26 27 | 12 mm | 50,0 | 14 |