

# K-WV 3/2 5/2 NAMUR LB LF

3/2- and 5/2-way spool valves with NAMUR style interface and air spring

**HANSA FLEX**

## 属性

适用介质	Air, neutral gases (filtered)
工作压力	1.5 to 10 bar (552.11 and 552.12); 2.5 to 10 bar (552.21 and 552.22)
工作温度	-20 °C to +50 °C
接口 1 - 3	G 1/4 (Port 1), G 1/4 (Port 3 and 5)
接口 1/3 + 5	G 1/4 (Port 1), G 1/4 (Port 3 and 5)
电接口	Plug connector PG 9
包含在供货范围内	Plug connector PG 9, conversion plate, screws and seal
功率消耗	3 W=/5 VA~
壳体	Anodised aluminium
滑座	Stainless steel
密封材料	NBR



## 提示

其它数据应客户要求提供。

## 描述

Pilot-operated 3/2- and 5/2-way spool valves with threaded ports and a NAMUR style interface with air purging function. By adding the conversion plate supplied with each valve, the device can be adapted to 3/2-way function.

Filter regulators are also available with bowl guard or metal bowl. Filter regulators are also available in lockable version. Please ask for more information.

## 货品

名称	电压	Port 1	接口 3 + 5	DN	流量 (L/min)
K- 07 15 00 13	230 V, 50 Hz	G 1/4	G 1/4	7	1250
K- 07 15 00 14	24 V DC	G 1/4	G 1/4	7	1250