


# K-VSTO POM

## Plugs

### 属性

|      |   |
|------|---|
| 工作压力 | 0 - 16 bar (4 - 8 mm); 0 - 10 bar (10 - 28 mm)    |
| 工作温度 | -20 °C to +70 °C in air; +1 °C to +70 °C in water |
| 原料   | Acetalpolymerisat (POM)                           |
| 密封材料 | NBR   |



### 提示

其它数据应客户要求提供。

### 描述

Lightweight, push-in fittings distinguished by high strength, toughness, resistance to abrasion and impact resistance - ideal for a wide range of applications. Plastic and metal tubes are connected together quickly and easily. Suitable for compressed air or liquids, with good resistance to a large number of chemicals.

### 货品

| 名称             | 颜色 | L1<br>(mm) | 接套<br>(mm) |
|----------------|----|------------|------------|
| K- 07 40 29 11 | 红色 | 28,0       | 4          |
| K- 07 40 29 12 | 红色 | 28,0       | 5          |
| K- 07 40 29 13 | 红色 | 30,0       | 6          |
| K- 07 40 29 14 | 红色 | 31,0       | 8          |
| K- 07 40 29 15 | 红色 | 36,5       | 10         |
| K- 07 40 29 16 | 红色 | 38,5       | 12         |
| K- 07 40 29 17 | 黑色 | 45,0       | 15         |
| K- 07 40 29 18 | 黑色 | 41,5       | 18         |
| K- 07 40 29 19 | 黑色 | 45,0       | 22         |
| K- 07 40 29 20 | 黑色 | 56,0       | 28         |