


K-VSTO POM

Plugs

属性

| | |
|------|---|
| 工作压力 | 0 - 16 bar (4 - 8 mm); 0 - 10 bar (10 - 28 mm) |
| 工作温度 | -20 °C to +70 °C in air; +1 °C to +70 °C in water |
| 原料 | Acetalpolymerisat (POM) |
| 密封材料 | NBR |



提示

其它数据应客户要求提供。

描述

Lightweight, push-in fittings distinguished by high strength, toughness, resistance to abrasion and impact resistance - ideal for a wide range of applications. Plastic and metal tubes are connected together quickly and easily. Suitable for compressed air or liquids, with good resistance to a large number of chemicals.

货品

| 名称 | 颜色 | L1 (mm) | 接套 (mm) |
|----------------|----|------------|------------|
| K- 07 40 29 11 | 红色 | 28,0 | 4 |
| K- 07 40 29 12 | 红色 | 28,0 | 5 |
| K- 07 40 29 13 | 红色 | 30,0 | 6 |
| K- 07 40 29 14 | 红色 | 31,0 | 8 |
| K- 07 40 29 15 | 红色 | 36,5 | 10 |
| K- 07 40 29 16 | 红色 | 38,5 | 12 |
| K- 07 40 29 17 | 黑色 | 45,0 | 15 |
| K- 07 40 29 18 | 黑色 | 41,5 | 18 |
| K- 07 40 29 19 | 黑色 | 45,0 | 22 |
| K- 07 40 29 20 | 黑色 | 56,0 | 28 |