

# K-SA MUFFE 16

Weld-on sleeve 16 made of black steel ST 37-2, DIN 2986 with continuous thread

**HANSA FLEX**

## 属性

|      |                     |
|------|---------------------|
| 工作压力 | Max. 50 bar         |
| 接口螺纹 | acc. ISO 7-1        |
| 原料   | black steel ST 37-2 |



## 提示

其它数据应客户要求提供。

## 描述

The steel fittings are made of tubular steel to DIN 2441 and boast good resistance to mechanical stresses. Hot dip galvanised steel fittings are completely coated with a layer of pure zinc and are therefore suitable for drinking water. They are also protected against rust. They are used in pipe construction, plumbing and gas installations as well as a wide range of industrial applications, especially in conjunction with the popular malleable iron series.

## 货品

| 名称             | 螺纹      | 长度<br>(mm) |
|----------------|---------|------------|
| K- 07 40 35 30 | R 1/4   | 25,0       |
| K- 07 40 35 33 | R 3/8   | 26,0       |
| K- 07 40 35 29 | R 1/2   | 34,0       |
| K- 07 40 35 32 | R 3/4   | 36,0       |
| K- 07 40 35 26 | R 1     | 43,0       |
| K- 07 40 35 28 | R 1 1/4 | 48,0       |
| K- 07 40 35 27 | R 1 1/2 | 48,0       |
| K- 07 40 35 31 | R 2     | 56,0       |
| K- 07 40 50 36 | R 2 1/2 | 65,0       |
| K- 07 40 50 37 | R 3     | 71,0       |