
## K-ZFL ABSP-KLAPPEN

## **Butterfly valves**



属性	
工作压力	Max. 16 bar
工作温度	-15 °C to +120 °C
适用介质	Water / steam, salt water, salt water, ester, ketone, alkali, caustic soda, sodium hydroxide. Not recommended for hydrocarbons
温度范围	-20 °C to +120 °C
売体	Grey cast iron GG25 epoxy resin coated, RAL 5015
密封	EPDM
轴	SS416
轴封	EPDM
手柄	GG25 epoxy resin coated





## 提示

其它数据应客户要求提供。

名称	<u>圆盘</u>	DN	B (mm)	H1 (mm)	H2 (mm)	H3 (mm)	L (mm)
K- 07 30 03 46	Stainless Steel CF8M/1.4404	50	47,0	71,0	143,0	236,0	100,0
K- 07 30 03 47	Stainless Steel CF8M/1.4404	65	49,0	78,0	155,0	255,0	115,0
K- 07 30 03 48	Stainless Steel CF8M/1.4404	80	47,0	89,0	162,0	273,0	127,0
K- 07 30 03 49	Stainless Steel CF8M/1.4404	100	56,0	102,0	178,0	302,0	163,0
K- 07 30 03 50	Stainless Steel CF8M/1.4404	125	59,0	123,0	191,0	336,0	190,0
K- 07 30 03 51	Stainless Steel CF8M/1.4404	150	59.0	138.0	205.0	365.0	216,0