


# K-STECKVERSCHR SK MINI

Male connectors, male thread with outer hex, mini

**HANSA FLEX**

## 属性

工作压力	Max. 10 bar, vacuum
应用范围	Air, vacuum
推荐的软管	PU or PA (nylon)
适用介质	压缩空气
标准	M thread acc. to DIN 13-1, with O-Ring G thread acc. to DIN EN ISO 228-1, with O-Ring R thread acc. to ISO 7-1, thread coating
温度范围	0 °C to +60 °C
密封面	O-ring (NBR)
原料	Plastic, Nickel plated brass
紧压环	Plastic



## 提示

其它数据应客户要求提供。

## 描述

Push-in fittings series manufactured in plastic and nickel-plated brass, space-saving miniature design.

## 货品

名称	螺纹	用于软管外径-Ø	L1 (mm)	SW
K- 07 40 23 16	M 3	3 mm	15,0	8 mm
K- 07 40 23 17	M 3	4 mm	17,5	8 mm
K- 07 40 23 18	M 5	3 mm	16,0	8 mm
K- 07 40 23 19	M 5	4 mm	18,5	8 mm
K- 07 40 23 20	M 5	6 mm	18,0	10 mm
K- 07 40 23 21	M 6	3 mm	15,0	10 mm
K- 07 40 23 22	M 6	4 mm	19,0	10 mm
K- 07 40 23 23	M 6	6 mm	18,5	10 mm
K- 07 40 23 24	G 1/8	4 mm	15,2	14 mm
K- 07 40 23 25	G 1/8	6 mm	17,2	13 mm
K- 07 40 23 26	R 1/8	4 mm	16,0	10 mm
K- 07 40 23 27	R 1/8	6 mm	18,5	10 mm