

# K-FI REGL METALLBEHAE V HW G

Filter regulators with metal bowl, sight glass and »HW« mounting bracket, fully-automatic drain valve

**HANSA FLEX**

## 属性

|             |  |
|-------------|--|
| 入口压力        | Max. 10 bar  |
| 介质温度        | max. 70 °C   |
| 环境温度        | Max. 70 °C   |
| 过滤元件中的气孔宽度  | 5 µm   |
| 密封材料        | NBR  |
| 弹簧罩         | POM  |
| 壳体          | Die-cast aluminium   |
| Drain valve | Semi- or fully-automatic                                       |
| 流量值测量       | At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p$ = 1 bar |
| 更多注明信息      | User manual on request   |



## 货品

| 名称             | 螺纹    | 调节范围        | 流量<br>(L/min) | A<br>(mm) | B        | C<br>(mm) | D<br>(mm) | 结构尺寸 |
|----------------|-------|-------------|---------------|-----------|----------|-----------|-----------|------|
| K- 07 25 07 06 | G 3/4 | 1.5 - 9 bar | 7000          | 85,0      | 363,0 mm | 144,0     | 219,0     | 600  |
| K- 07 25 07 08 | G 1   | 1.5 - 9 bar | 7000          | 85,0      | 363,0 mm | 144,0     | 219,0     | 600  |

## 附件

|                                     |   |
|-------------------------------------|---|
| K-VERSCHLEI-SATZ                    | Set of wearing parts                                    |
| K-ERSATZMEMBRANE                    | Replacement diaphragm                                   |
| K-ADAPTERPLATTEN HANSA              | Adapter plate HANSA                                     |
| K-ERSATZBEHAELTER G UND G-MINI POLY | Spare tanks »G« Series and »G-mini« Series Polycarbonat |
| K-FILTERELEMENT                     | Filter element  |
| K-HALTERBAUSATZ                     | Holder  |
| K-VERBINDUNGELEMENTE                | Connecting sets   |
| K-WANDHALTER                        | Wall bracket  |