
K-WTEH 2-TLG PC SCHU VARIOBLOC

Service units, 2-piece with polycarbonate bowl and bowl guard



属性				
入口压力	Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl)			
介质温度	max. 50 °C			
环境温度	Max. 50 °C (polycarbonate bowl), Max. 80 °C (metal bowl)			
过滤器元件中的气孔宽度	40 μm			
密封材料	NBR			
弹簧罩	POM			
売体	Die-cast zinc			
膜片	NBR			
泄水头	PA			
Drain valve	Manual			
流量值测量	At P1 = 10 bar, P2 = 6 bar and pressure drop Δp = 1 bar			
	-			





提示

其它数据应客户要求提供。

描述

Two or three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator. Approved series in modern industrial design, with the following key benefits: Simple handling, Convenient modular assembly thanks to innovative fasteners, Excellent flow values.

订购指南

Service units are also available with bowl guard or metal bowl. Service units are also available in other control ranges (0.5 - 6 bar and 0.5 - 16 bar) and in lockable version. Please ask for more information.

附加信息

Service units are also available with bowl guard or metal bowl. Service units are also available in other control ranges.

货品

名称	螺纹	调节范围	流量	Α	В	С
			(L/min)	(mm)		(mm)
K- 07 25 22 81	G 1/4	0.5 - 10 bar	1500	96,0	203,0 mm	68,0
K- 07 25 22 80	G 3/8	0.5 - 10 bar	1800	96,0	203,0 mm	68,0
K- 07 25 22 79	G 1/2	0.5 - 10 bar	3400	140,0	273,0 mm	98,0
K- 07 25 22 78	G 3/4	0.5 - 10 bar	5000	140,0	273,0 mm	98,0
K- 07 25 22 77	G 1	0.5 - 10 bar	5000	194,0	273,0 mm	98,0