
# K-WTEH 3-TLG PC SCHU VARIOBLOC

Service units, 3-piece with polycarbonate bowl and bowl guard



属性					
入口压力	Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl)				
介质温度	max. 50 °C				
环境温度	Max. 50 °C (polycarbonate bowl), Max. 80 °C (metal bowl)				
过滤器元件中的气孔宽度	40 μm				
密封材料	NBR				
弹簧罩	POM				
売体	Die-cast zinc				
膜片	NBR				
泄水头	PA				
Drain valve	Manual				
流量值测量	At P1 = 10 bar, P2 = 6 bar and pressure drop Δp = 1 bar				





# 提示

其它数据应客户要求提供。

#### 描述

Two or three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator. Approved series in modern industrial design, with the following key benefits: Simple handling, Convenient modular assembly thanks to innovative fasteners, Excellent flow values.

# 订购指南

Service units are also available with bowl guard or metal bowl. Service units are also available in other control ranges (0.5 - 6 bar and 0.5 - 16 bar) and in lockable version. Please ask for more information.

# 附加信息

Service units are also available with bowl guard or metal bowl. Service units are also available in other control ranges.

### 货品

名称	螺纹	调节范围	流量 (L/min)	A (mm)	В	C (mm)
K- 07 25 22 85	G 3/8	0.5 - 10 bar	1800	144,0	201,0 mm	68,0
K- 07 25 22 84	G 1/2	0.5 - 10 bar	3400	210,0	247,0 mm	98,0
K- 07 25 22 83	G 3/4	0.5 - 10 bar	5000	210,0	247,0 mm	98,0
K- 07 25 22 82	G 1	0.5 - 10 bar	5000	264,0	247,0 mm	98,0