

# K-LKM S NW7,4 DREH IG VA

Safety couplings DN 7.4, stainless steel 1.4404, female, swivel type

**HANSA*****FLEX***

## 属性

|      |   |
|------|---|
| 工作压力 | 最大 10 巴                                       |
| 空气流量 | 1.800 l/min (at 6 bar and $\Delta p = 1$ bar) |
| 介质温度 | -20 °C to +150 °C                             |
| 壳体   | Stainless steel 1.4404                        |
| 螺纹   | Stainless steel 1.4404                        |
| 内部部件 | Stainless steel 1.4404                        |
| 钮, 阀 | Stainless steel 1.4404                        |
| 密封材料 | FKM   |



## 提示

Not suitable for hitting / pulsating tools.

其它数据应客户要求提供。

## 描述

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414. For the food processing, chemical and medical industries as well as pharmaceutical plant construction.

## 附加信息

Not suitable for hitting / pulsating tools.

## 货品

| 名称             | 接口           | 长度<br>(mm) | SW<br>(mm) |
|----------------|--------------|------------|------------|
| K- 07 35 12 79 | G 1/4 female | 71,5       | 21         |
| K- 07 35 12 80 | G 3/8 female | 75,5       | 21         |
| K- 07 35 12 81 | G 1/2 female | 77,5       | 24         |