

K-ABSPV AG OR

Shut-off valves, double parallel thread with O-ring

HANSA FLEX

属性

| | |
|-------|--|
| 工作压力 | Max. 15 bar, coarse vacuum |
| 应用范围 | Air, vacuum |
| 推荐的软管 | PU or PA (nylon) |
| 适用介质 | Compressed air and all gases or liquids that are compatible with the materials |
| 温度范围 | -20 °C to +80 °C |
| 密封面 | Parallel version: O-ring in housing, Conical version: thread coating |
| 原料 | Plastic, Nickel plated brass |
| 紧压环 | Plastic |



提示

其它数据应客户要求提供。

描述

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

货品

| 名称 | 螺纹 1 | 螺纹 2 | L1 (mm) | L2 (mm) | SW |
|----------------|-------|-------|------------|------------|---------------|
| K- 07 40 08 10 | G 1/8 | G 1/8 | 64,5 | 42,6 | 14 mm |
| K- 07 40 08 09 | G 1/4 | G 1/8 | 67,6 | 42,6 | 17 mm / 14 mm |
| K- 07 40 08 08 | G 1/4 | G 1/4 | 67,6 | 42,6 | 17 mm |
| K- 07 40 08 11 | G 3/8 | G 1/4 | 81,1 | 47,0 | 20 mm / 20 mm |
| K- 07 40 08 12 | G 3/8 | G 3/8 | 82,4 | 47,0 | 20 mm / 20 mm |
| K- 07 40 08 07 | G 1/2 | G 3/8 | 86,2 | 47,0 | 24 mm / 21 mm |
| K- 07 40 08 06 | G 1/2 | G 1/2 | 89,0 | 47,0 | 24 mm |