
K-STECKVERBINDU RED

Reducers



属性		
工作压力	Max. 16 bar	
工作温度	-20 °C to +150 °C	
原料	黄铜镀镍	
紧压环	Nickel-plated brass	
张紧环	Stainless steel	





提示

其它数据应客户要求提供。

描述

Push-in fittings, manufactured entirely in nickel-plated brass. All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

Str>All parts with a parallel thread are supplied with an FPM O-ring.

货品

典 吅			
名称	用于软管外径-Ø	L1	
		(mm)	
K- 07 40 47 75	6 mm / 4 mm	33,0	
K- 07 40 47 76	8 mm / 6 mm	39,0	
K- 07 40 47 77	10 mm / 8 mm	39,5	
K- 07 40 47 78	12 mm / 10 mm	41,5	