

# K-SCHOTT-STECKVERB 3

Female bulkhead connectors

**HANSA FLEX**

## 属性

|       |  |
|-------|--|
| 工作压力  | Max. 15 bar, coarse vacuum   |
| 应用范围  | Air, vacuum  |
| 推荐的软管 | PU or PA (nylon)   |
| 适用介质  | Compressed air and all gases or liquids that are compatible with the materials |
| 温度范围  | -20 °C to +80 °C   |
| 原料    | Plastic, Nickel plated brass   |
| 紧压环   | Plastic  |



## 提示

其它数据应客户要求提供。

## 描述

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

## 货品

| 名称             | 用于软管外径-Ø | 配电板螺纹    | L1<br>(mm) | SW    |
|----------------|----------|----------|------------|-------|
| K- 07 40 04 31 | 4 mm     | M 12 x 1 | 31,1       | 14 mm |
| K- 07 40 04 32 | 6 mm     | M 14 x 1 | 33,4       | 17 mm |
| K- 07 40 04 33 | 8 mm     | M 16 x 1 | 37,7       | 19 mm |
| K- 07 40 04 34 | 10 mm    | M 20 x 1 | 41,8       | 24 mm |
| K- 07 40 04 35 | 12 mm    | M 22 x 1 | 46,7       | 27 mm |
| K- 07 40 04 36 | 16 mm    | M 27 x 1 | 51,2       | 32 mm |