


K-STECKVERSCHR AGR-K SK VA

Male connectors, conical male thread with outer hex

HANSA FLEX

属性

| | |
|---------|---|
| 脉冲工作压力 | Max. 10 bar |
| 压力 | Max. 15 bar (depending on pipe quality) |
| 合适的管件材料 | PVDF, PTFE, stainless steel, PA, PU |
| 标准 | R thread acc. to ISO 7-1 |
| 环境温度 | -20 °C to max. +150 °C (depending on pipe quality and diameter) |
| 原料 | 不锈钢 1.4404 |
| 密封材料 | FKM |



提示

其它数据应客户要求提供。

描述

For use with aggressive media and in areas with corrosive outside influences, in the food processing industry and in hygienic and sanitary applications.

货品

| 名称 | 螺纹 | 用于软管外径-Ø | L1 (mm) | SW |
|----------------|-------|----------|------------|-------|
| K- 07 40 24 10 | R 1/8 | 4 mm | 16,6 | 10 mm |
| K- 07 40 24 11 | R 1/8 | 6 mm | 21,2 | 12 mm |
| K- 07 40 24 12 | R 1/8 | 8 mm | 25,2 | 14 mm |
| K- 07 40 24 07 | R 1/4 | 4 mm | 20,6 | 14 mm |
| K- 07 40 24 08 | R 1/4 | 6 mm | 20,7 | 14 mm |
| K- 07 40 24 09 | R 1/4 | 8 mm | 23,7 | 14 mm |
| K- 07 40 24 06 | R 1/4 | 10 mm | 30,3 | 16 mm |
| K- 07 40 24 13 | R 3/8 | 10 mm | 23,5 | 17 mm |
| K- 07 40 24 14 | R 3/8 | 12 mm | 27,4 | 19 mm |
| K- 07 40 24 05 | R 1/2 | 12 mm | 27,4 | 22 mm |