

# K-L-STECKVER AG-K

Male elbows, conical male thread

**HANSA FLEX**

## 属性

|      |                  |
|------|------------------|
| 工作压力 | Max. 16 bar      |
| 工作温度 | -20 °C to +80 °C |
| 原料   | 黄铜镀镍             |
| 紧压环  | Hostaform        |
| 张紧环  | Stainless steel  |



## 提示

其它数据应客户要求提供。

## 描述

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series: Much easier connection and disconnection of the hose, even with repeated mounting, can also be used for non-calibrated hoses, suitable for vacuum operation.

## 货品

| 名称             | 螺纹    | 用于软管外径-Ø | L1<br>(mm) | L2<br>(mm) | SW    |
|----------------|-------|----------|------------|------------|-------|
| K- 07 40 25 65 | R 1/8 | 4 mm     | 18,6       | 16,0       | 10 mm |
| K- 07 40 25 66 | R 1/8 | 6 mm     | 21,9       | 16,0       | 10 mm |
| K- 07 40 25 67 | R 1/8 | 8 mm     | 25,4       | 16,0       | 10 mm |
| K- 07 40 25 63 | R 1/4 | 6 mm     | 21,9       | 18,5       | 10 mm |
| K- 07 40 25 64 | R 1/4 | 8 mm     | 25,4       | 18,5       | 10 mm |
| K- 07 40 25 62 | R 1/4 | 10 mm    | 27,2       | 22,0       | 14 mm |