

# K-STECKVERSCHR RU AGR OR

Male connectors, round, parallel male thread with O-ring and inner hex

**HANSA FLEX**

## 属性

工作压力	Max. 15 bar, coarse vacuum
应用范围	Air, vacuum
推荐的软管	PU or PA (nylon)
适用介质	Compressed air and all gases or liquids that are compatible with the materials
温度范围	-20 °C to +80 °C
密封面	Parallel version: O-ring in housing
原料	Plastic, Nickel plated brass
紧压环	Plastic



## 提示

其它数据应客户要求提供。

## 描述

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

## 货品

名称	螺纹	用于软管外径-Ø	内六角 (mm)	L1 (mm)
K- 07 40 09 07	M 5	4 mm	2,0	20,8
K- 07 40 09 08	M 5	6 mm	2,0	22,4
K- 07 40 09 20	G 1/8	4 mm	3,0	19,3
K- 07 40 09 21	G 1/8	6 mm	4,0	20,2
K- 07 40 09 22	G 1/8	8 mm	5,0	27,0
K- 07 40 09 18	G 1/8	10 mm	5,0	28,9
K- 07 40 09 19	G 1/8	12 mm	5,0	31,6
K- 07 40 09 15	G 1/4	4 mm	3,0	18,0
K- 07 40 09 16	G 1/4	6 mm	4,0	20,9
K- 07 40 09 17	G 1/4	8 mm	5,0	23,0
K- 07 40 09 13	G 1/4	10 mm	6,0	29,9
K- 07 40 09 14	G 1/4	12 mm	6,0	32,6
K- 07 40 09 26	G 3/8	6 mm	4,0	19,5
K- 07 40 09 27	G 3/8	8 mm	6,0	22,1
K- 07 40 09 23	G 3/8	10 mm	8,0	25,9
K- 07 40 09 24	G 3/8	12 mm	8,0	28,6
K- 07 40 09 25	G 3/8	16 mm	8,0	35,1
K- 07 40 09 12	G 1/2	8 mm	6,0	24,1
K- 07 40 09 09	G 1/2	10 mm	8,0	25,3
K- 07 40 09 10	G 1/2	12 mm	8,0	31,1
K- 07 40 09 11	G 1/2	16 mm	10,0	38,1