


# K-STECKVERSCHR IG SK 2

Female connectors, parallel female thread with outer hex

**HANSA FLEX**

## 属性

工作压力	Max. 15 bar, coarse vacuum
应用范围	Air, vacuum
推荐的软管	PU or PA (nylon)
适用介质	Compressed air and all gases or liquids that are compatible with the materials
温度范围	-20 °C to +80 °C
原料	Plastic, Nickel plated brass
紧压环	Plastic



## 提示

其它数据应客户要求提供。

## 描述

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

## 货品

名称	螺纹	用于软管外径-Ø	L1 (mm)	SW
K- 07 40 01 20	M 5	4 mm	21,3	10 mm
K- 07 40 01 21	M 5	6 mm	22,2	12 mm
K- 07 40 01 31	G 1/8	4 mm	23,8	14 mm
K- 07 40 01 32	G 1/8	6 mm	25,2	14 mm
K- 07 40 01 33	G 1/8	8 mm	27,1	14 mm
K- 07 40 41 28	G 1/8	10 mm	28,5	14 mm
K- 07 40 01 28	G 1/4	4 mm	26,8	17 mm
K- 07 40 01 29	G 1/4	6 mm	28,2	17 mm
K- 07 40 01 30	G 1/4	8 mm	30,1	17 mm
K- 07 40 01 26	G 1/4	10 mm	32,2	17 mm
K- 07 40 01 27	G 1/4	12 mm	34,6	21 mm
K- 07 40 01 36	G 3/8	6 mm	29,2	21 mm
K- 07 40 01 37	G 3/8	8 mm	31,1	21 mm
K- 07 40 01 34	G 3/8	10 mm	33,4	21 mm
K- 07 40 01 35	G 3/8	12 mm	35,6	21 mm
K- 07 40 01 24	G 1/2	6 mm	31,2	24 mm
K- 07 40 01 25	G 1/2	8 mm	33,1	24 mm
K- 07 40 01 22	G 1/2	10 mm	35,2	24 mm
K- 07 40 01 23	G 1/2	12 mm	37,6	24 mm
K- 07 40 41 27	G 1/2	16 mm	39,7	24 mm