
K-STECKVERSCHR IG SK 2


Female connectors, parallel female thread with outer hex

HANSA FLEX

属性

工作压力	Max. 15 bar, coarse vacuum
应用范围	Air, vacuum
推荐的软管	PU or PA (nylon)
适用介质	Compressed air and all gases or liquids that are compatible with the materials
温度范围	-20 °C to +80 °C
原料	Plastic, Nickel plated brass
紧压环	Plastic





提示

其它数据应客户要求提供。

描述

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

货品

名称	螺纹	用于软管外径-Ø	L1 (mm)	SW
K- 07 40 01 20	M 5	4 mm	21,3	10 mm
K- 07 40 01 21	M 5	6 mm	22,2	12 mm
K- 07 40 01 31	G 1/8	4 mm	23,8	14 mm
K- 07 40 01 32	G 1/8	6 mm	25,2	14 mm
K- 07 40 01 33	G 1/8	8 mm	27,1	14 mm
K- 07 40 41 28	G 1/8	10 mm	28,5	14 mm
K- 07 40 01 28	G 1/4	4 mm	26,8	17 mm
K- 07 40 01 29	G 1/4	6 mm	28,2	17 mm
K- 07 40 01 30	G 1/4	8 mm	30,1	17 mm
K- 07 40 01 26	G 1/4	10 mm	32,2	17 mm
K- 07 40 01 27	G 1/4	12 mm	34,6	21 mm
K- 07 40 01 36	G 3/8	6 mm	29,2	21 mm
K- 07 40 01 37	G 3/8	8 mm	31,1	21 mm
K- 07 40 01 34	G 3/8	10 mm	33,4	21 mm
K- 07 40 01 35	G 3/8	12 mm	35,6	21 mm
K- 07 40 01 24	G 1/2	6 mm	31,2	24 mm
K- 07 40 01 25	G 1/2	8 mm	33,1	24 mm
K- 07 40 01 22	G 1/2	10 mm	35,2	24 mm
K- 07 40 01 23	G 1/2	12 mm	37,6	24 mm
K- 07 40 41 27	G 1/2	16 mm	39,7	24 mm

尽管经过了仔细审阅,但我们无法完全排除发生错误的可能,对所提供的信息数据本公司不承担任何责任。