

K-T-STECK VERS DRE AG OR 2

Male branch tees, swivel type, parallel male thread with O-ring

HANSA FLEX

属性

| | |
|-------|--|
| 工作压力 | Max. 15 bar, coarse vacuum |
| 应用范围 | Air, vacuum |
| 推荐的软管 | PU or PA (nylon) |
| 适用介质 | Compressed air and all gases or liquids that are compatible with the materials |
| 温度范围 | -20 °C to +80 °C |
| 密封面 | Parallel version: O-ring in housing |
| 原料 | Plastic, Nickel plated brass |
| 紧压环 | Plastic |



提示

其它数据应客户要求提供。

描述

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

货品

| 名称 | 螺纹 | 用于软管外径-Ø | L1 (mm) | L2 (mm) | SW |
|----------------|-------|----------|------------|------------|-------|
| K- 07 40 02 59 | M 5 | 4 mm | 36,0 | 21,1 | 8 mm |
| K- 07 40 02 60 | M 5 | 6 mm | 40,0 | 22,2 | 8 mm |
| K- 07 40 02 71 | G 1/8 | 4 mm | 36,0 | 19,0 | 14 mm |
| K- 07 40 02 72 | G 1/8 | 6 mm | 40,0 | 20,1 | 14 mm |
| K- 07 40 02 73 | G 1/8 | 8 mm | 45,4 | 25,7 | 14 mm |
| K- 07 40 02 68 | G 1/4 | 4 mm | 36,0 | 19,0 | 17 mm |
| K- 07 40 02 69 | G 1/4 | 6 mm | 40,0 | 20,1 | 17 mm |
| K- 07 40 02 70 | G 1/4 | 8 mm | 45,4 | 21,7 | 17 mm |
| K- 07 40 02 66 | G 1/4 | 10 mm | 53,8 | 27,6 | 17 mm |
| K- 07 40 02 67 | G 1/4 | 12 mm | 58,6 | 28,9 | 17 mm |
| K- 07 40 02 77 | G 3/8 | 6 mm | 40,0 | 21,2 | 20 mm |
| K- 07 40 02 78 | G 3/8 | 8 mm | 45,4 | 22,8 | 20 mm |
| K- 07 40 02 74 | G 3/8 | 10 mm | 53,8 | 24,6 | 20 mm |
| K- 07 40 02 75 | G 3/8 | 12 mm | 58,6 | 25,9 | 20 mm |
| K- 07 40 02 76 | G 3/8 | 16 mm | 69,0 | 34,2 | 20 mm |
| K- 07 40 02 64 | G 1/2 | 6 mm | 40,0 | 23,6 | 24 mm |
| K- 07 40 02 65 | G 1/2 | 8 mm | 45,4 | 25,2 | 24 mm |
| K- 07 40 02 61 | G 1/2 | 10 mm | 53,8 | 26,5 | 24 mm |
| K- 07 40 02 62 | G 1/2 | 12 mm | 58,6 | 27,8 | 24 mm |
| K- 07 40 02 63 | G 1/2 | 16 mm | 69,0 | 30,9 | 24 mm |