

# K-T-STECK VERS DRE AG OR 2

Male branch tees, swivel type, parallel male thread with O-ring

**HANSA FLEX**

## 属性

工作压力	Max. 15 bar, coarse vacuum
应用范围	Air, vacuum
推荐的软管	PU or PA (nylon)
适用介质	Compressed air and all gases or liquids that are compatible with the materials
温度范围	-20 °C to +80 °C
密封面	Parallel version: O-ring in housing
原料	Plastic, Nickel plated brass
紧压环	Plastic



## 提示

其它数据应客户要求提供。

## 描述

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

## 货品

名称	螺纹	用于软管外径-Ø	L1 (mm)	L2 (mm)	SW
K- 07 40 02 59	M 5	4 mm	36,0	21,1	8 mm
K- 07 40 02 60	M 5	6 mm	40,0	22,2	8 mm
K- 07 40 02 71	G 1/8	4 mm	36,0	19,0	14 mm
K- 07 40 02 72	G 1/8	6 mm	40,0	20,1	14 mm
K- 07 40 02 73	G 1/8	8 mm	45,4	25,7	14 mm
K- 07 40 02 68	G 1/4	4 mm	36,0	19,0	17 mm
K- 07 40 02 69	G 1/4	6 mm	40,0	20,1	17 mm
K- 07 40 02 70	G 1/4	8 mm	45,4	21,7	17 mm
K- 07 40 02 66	G 1/4	10 mm	53,8	27,6	17 mm
K- 07 40 02 67	G 1/4	12 mm	58,6	28,9	17 mm
K- 07 40 02 77	G 3/8	6 mm	40,0	21,2	20 mm
K- 07 40 02 78	G 3/8	8 mm	45,4	22,8	20 mm
K- 07 40 02 74	G 3/8	10 mm	53,8	24,6	20 mm
K- 07 40 02 75	G 3/8	12 mm	58,6	25,9	20 mm
K- 07 40 02 76	G 3/8	16 mm	69,0	34,2	20 mm
K- 07 40 02 64	G 1/2	6 mm	40,0	23,6	24 mm
K- 07 40 02 65	G 1/2	8 mm	45,4	25,2	24 mm
K- 07 40 02 61	G 1/2	10 mm	53,8	26,5	24 mm
K- 07 40 02 62	G 1/2	12 mm	58,6	27,8	24 mm
K- 07 40 02 63	G 1/2	16 mm	69,0	30,9	24 mm