

# K-L-STECKVER IG-K DREH

Banjo elbows with conical female thread, swivel type

**HANSA FLEX**

## 属性

工作压力	Max. 15 bar, coarse vacuum
应用范围	Air, vacuum
推荐的软管	PU or PA (nylon)
适用介质	Compressed air and all gases or liquids that are compatible with the materials
温度范围	-20 °C to +80 °C
密封面	Conical version: thread coating
原料	Plastic, Nickel plated brass
紧压环	Plastic



## 提示

其它数据应客户要求提供。

## 描述

Push-in fittings series manufactured in plastic and nickel-plated brass. All parts are suitable for use with hoses, tubes or pipes made of plastic and copper.

## 货品

名称	螺纹	用于软管外径-Ø	L1 (mm)	L2 (mm)	SW
K- 07 40 04 63	Rc 1/8	4 mm	17,5	23,0	14 mm
K- 07 40 04 64	Rc 1/8	6 mm	19,0	24,4	14 mm
K- 07 40 04 65	Rc 1/8	8 mm	22,8	27,3	14 mm
K- 07 40 04 62	Rc 1/8	10 mm	27,2	27,3	17 mm
K- 07 40 04 59	Rc 1/4	4 mm	17,5	26,0	17 mm
K- 07 40 04 60	Rc 1/4	6 mm	19,0	27,4	17 mm
K- 07 40 04 61	Rc 1/4	8 mm	22,8	30,3	17 mm
K- 07 40 04 57	Rc 1/4	10 mm	27,2	34,3	17 mm
K- 07 40 04 58	Rc 1/4	12 mm	29,6	37,0	21 mm
K- 07 40 04 69	Rc 3/8	6 mm	19,0	28,7	21 mm
K- 07 40 04 70	Rc 3/8	8 mm	22,8	32,0	21 mm
K- 07 40 04 66	Rc 3/8	10 mm	27,2	36,3	21 mm
K- 07 40 04 67	Rc 3/8	12 mm	29,6	38,0	21 mm
K- 07 40 04 68	Rc 3/8	16 mm	32,5	40,5	24 mm
K- 07 40 04 56	Rc 1/2	8 mm	22,8	34,3	24 mm
K- 07 40 04 53	Rc 1/2	10 mm	27,2	38,8	24 mm
K- 07 40 04 54	Rc 1/2	12 mm	29,6	40,5	24 mm
K- 07 40 04 55	Rc 1/2	16 mm	32,5	43,0	24 mm