


K-T-STECK VERS DRE AG OR

Male branch tees, swivel type, parallel male thread with O-ring

HANSA FLEX

属性

| | |
|------|---------------------|
| 工作压力 | Max. 16 bar |
| 工作温度 | -20 °C to +150 °C |
| 原料 | 黄铜镀镍 |
| 紧压环 | Nickel-plated brass |
| O 形圈 | FKM (FPM) |
| 张紧环 | Stainless steel |



提示

其它数据应客户要求提供。

描述

Push-in fittings, manufactured entirely in nickel-plated brass. All parts with a parallel thread are supplied with an FPM O-ring. All parts with conical threads are coated with preCOTE 5 dispersion, all fittings in this series can thus also be used at high temperatures (medium compressed air).

货品

| 名称 | 螺纹 | 用于软管外径-Ø | L1 (mm) | L2 (mm) | SW |
|----------------|-------|----------|------------|------------|-------|
| K- 07 40 27 80 | G 1/8 | 4 mm | 40,0 | 20,0 | 13 mm |
| K- 07 40 27 81 | G 1/8 | 6 mm | 43,0 | 20,0 | 13 mm |
| K- 07 40 27 82 | G 1/8 | 8 mm | 47,0 | 20,0 | 13 mm |
| K- 07 40 27 78 | G 1/4 | 6 mm | 43,0 | 24,0 | 13 mm |
| K- 07 40 27 79 | G 1/4 | 8 mm | 47,0 | 24,0 | 13 mm |
| K- 07 40 27 77 | G 1/4 | 10 mm | 53,0 | 24,0 | 16 mm |
| K- 07 40 27 84 | G 3/8 | 8 mm | 47,0 | 25,5 | 13 mm |
| K- 07 40 27 83 | G 3/8 | 10 mm | 53,0 | 28,0 | 16 mm |
| K- 07 40 47 89 | G 3/8 | 12 mm | 58,0 | 28,5 | 20 mm |
| K- 07 40 47 88 | G 1/2 | 12 mm | 58,0 | 33,5 | 20 mm |