

# K-WERKST-SCHLAUCH SOFT

Workshop hose soft

**HANSA FLEX**

## 属性

内胶层	Soft-PVC, black
增强层	聚酯编织
外胶层	Soft-PVC, blue
温度	-20 °C to +60 °C
卷长	50 m



## 提示

其它数据应客户要求提供。

## 描述

Highly flexible hose for compressed air applications in workshop areas (compressed air feed for pneumatic tools, equipping assembly stations, etc.). Thanks to the even fabric reinforcement, this hose combines high pressure resistance, very good handling and high mechanical strength with excellent bond adhesion. The high level of ozone resistance further enhances the hose's durability and reliability. TÜV approved.

## 货品

名称	软管内径 Ø (mm)	软管外径 Ø (mm)	Max. working pressure resistance at 23°C (bar)	最小弯曲半径 (mm)
K- 07 10 10 33	6,3	11,0	15	23
K- 07 10 10 34	8,0	13,0	15	28
K- 07 10 10 35	9,0	14,5	15	32
K- 07 10 10 36	10,0	15,5	15	35
K- 07 10 10 37	12,7	19,0	15	45
K- 07 10 10 38	16,0	23,0	15	56
K- 07 10 10 39	19,0	26,5	15	67
K- 07 10 10 40	25,0	33,5	15	88