K-WERKST-SCHLAUCH SOFT

Workshop hose soft

HANSA FLEX

属性

内胶层	Soft-PVC, black
增强层	聚酯编织
外胶层	Soft-PVC, blue
温度	-20 °C to +60 °C
卷长	50 m



提示

其它数据应客户要求提供。

描述

Highly flexible hose for compressed air applications in workshop areas (compressed air feed for pneumatic tools, equipping assembly stations, etc.). Thanks to the even fabric reinforcement, this hose combines high pressure resistance, very good handling and high mechanical strength with excellent bond adhesion. The high level of ozone resistance further enhances the hose's durability and reliability. TÜV approved.

货品

名称	软管内径 Ø (mm)	软管外径 Ø (mm)	Max. working pressure resistance at 23°C (bar)	最小弯曲半径 (mm)
K- 07 10 10 33	6,3	11,0	15	23
K- 07 10 10 34	8,0	13,0	15	28
K- 07 10 10 35	9,0	14,5	15	32
K- 07 10 10 36	10,0	15,5	15	35
K- 07 10 10 37	12,7	19,0	15	45
K- 07 10 10 38	16,0	23,0	15	56
K- 07 10 10 39	19,0	26,5	15	67
K- 07 10 10 40	25,0	33,5	15	88

尽管经过了仔细审阅,但我们无法完全排除发生错误的可能,对所提供的信息数据本公司不承担任何责任。