

K-DURCHGANGSVERTEILERDOSE

Through porting box with through-hole thread, PN 15

HANSA FLEX

属性

| | |
|---------|--------------------------------|
| 工作压力 | Max. 15 bar |
| 固定扭矩 | 4 Nm |
| MS 螺纹扭矩 | 12 Nm |
| 温度范围 | -10 °C to +50 °C |
| 壳体 | Glass fibre-reinforced plastic |
| 螺纹 | Brass |



提示

其它数据应客户要求提供。

描述

1, 2 or 3-way porting boxes made of high-strength glass fibre-reinforced plastic for a wide range of applications. Available with up to 3 couplings and 2 inlet thread sizes. Optional through-hole thread at the bottom to facilitate the passage of the medium. All porting boxes have a robust, brass threaded insert for high tightening torques, TÜV certified. Suitable for almost any pneumatic application.

货品

| 名称 | 螺纹 入口 | 通孔螺纹 | 接口螺纹 |
|----------------|--------|-------|-----------|
| K- 07 40 48 04 | G 1/2" | G 1/2 | 1 x G 1/2 |
| K- 07 40 48 05 | G 1/2" | G 1/2 | 2 x G 1/2 |
| K- 07 40 48 06 | G 1/2" | G 1/2 | 3 x G 1/2 |
| K- 07 40 48 07 | G 3/4" | G 3/4 | 1 x G 1/2 |
| K- 07 40 48 08 | G 3/4" | G 3/4 | 2 x G 1/2 |
| K- 07 40 48 09 | G 3/4" | G 3/4 | 3 x G 1/2 |