K-DURCHGANGSVERTEILERDOSE

Through porting box with through-hole thread, PN 15

属性

工作压力	Max. 15 bar
固定扭矩	4 Nm
MS 螺纹扭矩	12 Nm
温度范围	-10 °C to +50 °C
壳体	Glass fibre-reinforced plastic
螺纹	Brass



提示

其它数据应客户要求提供。

描述

1, 2 or 3-way porting boxes made of high-strength glass fibre-reinforced plastic for a wide range of applications. Available with up to 3 couplings and 2 inlet thread sizes. Optional through-hole thread at the bottom to facilitate the passage of the medium. All porting boxes have a robust, brass threaded insert for high tightening torques, TÜV certified. Suitable for almost any pneumatic application.

货品

名称	螺纹 入口	通孔螺纹	接口螺纹
K- 07 40 48 04	G 1/2"	G 1/2	1 x G 1/2
K- 07 40 48 05	G 1/2"	G 1/2	2 x G 1/2
K- 07 40 48 06	G 1/2"	G 1/2	3 x G 1/2
K- 07 40 48 07	G 3/4"	G 3/4	1 x G 1/2
K- 07 40 48 08	G 3/4"	G 3/4	2 x G 1/2
K- 07 40 48 09	G 3/4"	G 3/4	3 x G 1/2

尽管经过了仔细审阅,但我们无法完全排除发生错误的可能,对所提供的信息数据本公司不承担任何责任。