

K-ROHRDOPPELNIPPEL VA

Double pipe nipples, stainless steel 1.4571

HANSA FLEX

属性

| | |
|------|----------------------|
| 工作压力 | Max. 20 bar |
| 接口螺纹 | R-thread to EN 10226 |
| 原料 | 不锈钢 1.4571 |



提示

The dimensions of the standard screw fittings may change slightly during the life of the catalogue as a result of optimisation processes. 其它数据应客户要求提供。

货品

| 名称 | 螺纹 | 长度 (mm) |
|----------------|---------|------------|
| K- 07 40 48 61 | R 1/4 | 40,0 |
| K- 07 40 48 62 | R 1/4 | 60,0 |
| K- 07 40 48 63 | R 1/4 | 80,0 |
| K- 07 40 48 56 | R 1/4 | 100,0 |
| K- 07 40 48 57 | R 1/4 | 120,0 |
| K- 07 40 48 58 | R 1/4 | 150,0 |
| K- 07 40 48 59 | R 1/4 | 180,0 |
| K- 07 40 48 60 | R 1/4 | 200,0 |
| K- 07 40 48 85 | R 3/8 | 40,0 |
| K- 07 40 48 86 | R 3/8 | 60,0 |
| K- 07 40 48 87 | R 3/8 | 80,0 |
| K- 07 40 48 80 | R 3/8 | 100,0 |
| K- 07 40 48 81 | R 3/8 | 120,0 |
| K- 07 40 48 82 | R 3/8 | 150,0 |
| K- 07 40 48 83 | R 3/8 | 180,0 |
| K- 07 40 48 84 | R 3/8 | 200,0 |
| K- 07 40 48 53 | R 1/2 | 40,0 |
| K- 07 40 48 54 | R 1/2 | 60,0 |
| K- 07 40 48 55 | R 1/2 | 80,0 |
| K- 07 40 48 48 | R 1/2 | 100,0 |
| K- 07 40 48 49 | R 1/2 | 120,0 |
| K- 07 40 48 50 | R 1/2 | 150,0 |
| K- 07 40 48 51 | R 1/2 | 180,0 |
| K- 07 40 48 52 | R 1/2 | 200,0 |
| K- 07 40 48 77 | R 3/4 | 40,0 |
| K- 07 40 48 78 | R 3/4 | 60,0 |
| K- 07 40 48 79 | R 3/4 | 80,0 |
| K- 07 40 48 72 | R 3/4 | 100,0 |
| K- 07 40 48 73 | R 3/4 | 120,0 |
| K- 07 40 48 74 | R 3/4 | 150,0 |
| K- 07 40 48 75 | R 3/4 | 180,0 |
| K- 07 40 48 76 | R 3/4 | 200,0 |
| K- 07 40 48 29 | R 1 | 40,0 |
| K- 07 40 48 30 | R 1 | 60,0 |
| K- 07 40 48 31 | R 1 | 80,0 |
| K- 07 40 40 93 | R 1 | 150,0 |
| K- 07 40 48 25 | R 1 | 100,0 |
| K- 07 40 48 26 | R 1 | 120,0 |
| K- 07 40 48 27 | R 1 | 180,0 |
| K- 07 40 48 28 | R 1 | 200,0 |
| K- 07 40 48 45 | R 1 1/4 | 40,0 |
| K- 07 40 48 46 | R 1 1/4 | 60,0 |
| K- 07 40 48 47 | R 1 1/4 | 80,0 |
| K- 07 40 48 40 | R 1 1/4 | 100,0 |
| K- 07 40 48 41 | R 1 1/4 | 120,0 |



尽管经过了仔细审阅,但我们无法完全排除发生错误的可能,对所提供的信息数据本公司不承担任何责任。

11.07.2026

HANSA-FLEX AG

www.hansa-flex.com

1

K-ROHRDOPPELNIPPEL VA

Double pipe nipples, stainless steel 1.4571

货品

| 名称 | 螺纹 | 长度 (mm) |
|----------------|---------|------------|
| K- 07 40 48 42 | R 1 1/4 | 150,0 |
| K- 07 40 48 43 | R 1 1/4 | 180,0 |
| K- 07 40 48 44 | R 1 1/4 | 200,0 |
| K- 07 40 48 37 | R 1 1/2 | 40,0 |
| K- 07 40 48 38 | R 1 1/2 | 60,0 |
| K- 07 40 48 39 | R 1 1/2 | 80,0 |
| K- 07 40 48 32 | R 1 1/2 | 100,0 |
| K- 07 40 48 33 | R 1 1/2 | 120,0 |
| K- 07 40 48 34 | R 1 1/2 | 150,0 |
| K- 07 40 48 35 | R 1 1/2 | 180,0 |
| K- 07 40 48 36 | R 1 1/2 | 200,0 |
| K- 07 40 48 69 | R 2 | 40,0 |
| K- 07 40 48 70 | R 2 | 60,0 |
| K- 07 40 48 71 | R 2 | 80,0 |
| K- 07 40 48 64 | R 2 | 100,0 |
| K- 07 40 48 65 | R 2 | 120,0 |
| K- 07 40 48 66 | R 2 | 150,0 |
| K- 07 40 48 67 | R 2 | 180,0 |
| K- 07 40 48 68 | R 2 | 200,0 |