

# K-SPIR SCHL KUPPL SET STANDARD

Spiral hose and coupling kit with standard coupling

**HANSA FLEX**

## 属性

应用	Air, gases, oils, greases, fuels, organic and inorganic substances
工作温度	-40 °C to +100 °C
接口类型	connection nipples and coupling NW 7,2



## 提示

其它数据应客户要求提供。

## 描述

These hoses allow gaseous and liquid media to flow safely and efficiently (Air, gases, oils, greases, fuels, organic and inorganic substances). Thanks to their small coil diameter, they are compact, easy to handle and lightweight. Very good recoil force owing to the use of nylon 12 (PA).

## 货品

名称	软管内径 Ø (mm)	软管外径 Ø (mm)	螺旋管外径 Ø (mm)	绕组	Max. working pressure resistance at 23°C (bar)	最大工作长度 (m)
K- 07 10 12 95	6,3	7,9	75	15	13	2,5
K- 07 10 12 96	6,3	7,9	75	30	13	5,0
K- 07 10 12 97	6,3	7,9	75	45	13	7,5
K- 07 10 12 65	7,9	9,5	115	10	12	2,5
K- 07 10 12 66	7,9	9,5	115	20	12	5,0
K- 07 10 12 67	7,9	9,5	115	30	12	7,5
K- 07 10 12 68	9,5	11,8	140	8	11	2,5
K- 07 10 12 69	9,5	11,8	140	15	11	5,0
K- 07 10 12 70	9,5	11,8	140	23	11	7,5

## 附件

K-DREHBARE VERSCHR KNICK	Swivel adapters with kink protector
K-STARRE VERSCHRAUBUNG	Rigid adapters with kink protector