# K-SPIR SCHL KUPPL SET STANDARD

Spiral hose and coupling kit with standard coupling

## 属性

| | |
|---|---|
| **应用** | Air, gases, oils, greases, fuels, organic and inorganic substances |
| **工作温度** | -40 °C to +100 °C |
| **接口类型** | connection nipples and coupling NW 7,2 |



## 提示

其它数据应客户要求提供。

## 描述

These hoses allow gaseous and liquid media to flow safely and efficiently (Air, gases, oils, greases, fuels, organic and inorganic substances). Thanks to their small coil diameter, they are compact, easy to handle and lightweight. Very good recoil force owing to the use of nylon 12 (PA).

## 货品

| 名称 | 软管内径 Ø (mm) | 软管外径 Ø (mm) | 螺旋管外径 Ø (mm) | 绕组 | Max. working pressure resistance at 23°C (bar) | 最大工作长度 (m) |
|---|---|---|---|---|---|---|
| **K- 07 10 12 95** | 6,3 | 7,9 | 75 | 15 | 13 | 2,5 |
| **K- 07 10 12 96** | 6,3 | 7,9 | 75 | 30 | 13 | 5,0 |
| **K- 07 10 12 97** | 6,3 | 7,9 | 75 | 45 | 13 | 7,5 |
| **K- 07 10 12 65** | 7,9 | 9,5 | 115 | 10 | 12 | 2,5 |
| **K- 07 10 12 66** | 7,9 | 9,5 | 115 | 20 | 12 | 5,0 |
| **K- 07 10 12 67** | 7,9 | 9,5 | 115 | 30 | 12 | 7,5 |
| **K- 07 10 12 68** | 9,5 | 11,8 | 140 | 8 | 11 | 2,5 |
| **K- 07 10 12 69** | 9,5 | 11,8 | 140 | 15 | 11 | 5,0 |
| **K- 07 10 12 70** | 9,5 | 11,8 | 140 | 23 | 11 | 7,5 |

## 附件

| | |
|---|---|
| **K-DREHBARE VERSCHR KNICK** | Swivel adapters with kink protector |
| **K-STARRE VERSCHRAUBUNG** | Rigid adapters with kink protector |

*尽管经过了仔细审阅,但我们无法完全排除发生错误的可能,对所提供的信息数据本公司不承担任何责任。*