K-SPIR SCHL KUPPL SET LKM NW 7,4
Spiral hose and coupling kit with pushbutton-type safety coupling (DN 7.4) and push-in plug, galvanised steel



属性	
接口类型	with pushbutton safety coupling NW 7,4 steel nippl galvanised
工作温度	-40 °C to +74 °C



www.hansa-flex.com

## 提示

其它数据应客户要求提供。

### 描述

Standard type or with braided reinforcements for high pressures. These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional nylon spiral hose, but with less tendency to loop and significantly better resistance to abrasion. There is consequently less danger of scratching coated or sensitive surfaces. The hose is extremely flexible and non-kinking. 不适合打击式和脉冲式工具!

#### 货品

→ nn							
名称	软管内径 Ø	软管外径 Ø (mm)	外绕组直径 Ø	Max. working pressure resistance at 23°C (bar)	最大工作长度 (m)		
K- 07 10 12 71	5,0	8,0	40	10	3,0		
K- 07 10 12 73	5,0	8,0	40	10	6,0		
K- 07 10 12 75	5,0	8,0	40	10	7,5		
K- 07 10 12 80	6,3	9,5	60	10	3,0		
K- 07 10 12 82	6,3	9,5	60	10	6,0		
K- 07 10 12 84	6,3	9,5	60	10	7,5		
K- 07 10 12 78	6,3	9,5	60	10	10,0		
K- 07 10 12 89	8,0	12,0	80	9	3,0		
K- 07 10 12 91	8,0	12,0	80	9	6,0		
K- 07 10 12 93	8,0	12,0	80	9	7,5		
K- 07 10 12 87	8,0	12,0	80	9	10,0		

# 附件

K-DREHBARE VERSCHRAUBUNG Swivel adapters