

# K-W90 STECK VB WAND 20-63 INFI

90°-elbow push-in connector Ø 20 mm – Ø 63 mm with wall mounting (adjustable)

**HANSA FLEX**

## 属性

适用介质	Compressed air, vacuum, inert gases
工作压力	-0,99 bar - 15 bar
温度范围	-20 °C to +80 °C
密封	NBR
壳体	Nickel-plated brass
夹紧环	Stainless steel 1.4301
螺母	Nickel-plated brass
O 形圈	NBR
防护垫圈	Technopolymer



## 货品

名称	管外径 Ø	接口	B	C	E	L1	L2	L3	L 最大	L 最小	M	N	O	SW1	SW2
			(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
K- 07 40 54 11	20 mm	G 1/2"	31,5	19,5	34,5	35,0	51,0	35,0	40	22	64	50	20,0	21	30
K- 07 40 54 12	25 mm	G 3/4	38,5	23,0	42,5	37,0	62,0	39,0	40	22	64	50	20,0	26	35
K- 07 40 54 13	32 mm	G 1	46,0	28,0	52,0	41,0	74,5	48,5	40	26	64	50	20,0	34	45