K-DIGIT DRUCKSCHA H 3DURCHF IA PF2A

Digital Flow Switch PF2A

HANSA FLEX

属性

结构类型	Digital Flow Switch
最大工作压力	0,1 MPa
额定电压	24 V DC
运行显示	3 digits, 7-Segment-LED lights at output signal = ON: OUT1: green, OUT2: red)
I/O 线缆	without connection cable
保护等级	IP 65
介质温度	0 °C to +50 °C
环境温度	0 °C to +50 °C
适用介质	Air and nitrogen
系列	PF2A
更多注明信息	for High flow Integrated Display Type



描述

Digital flow switch for high flow, series PF2A, for air and nitrogen, with integrated display unit, measuring range 150 to 3000 l/min, smallest adjustment unit 5 l/min, media temperature 0 to 50 °C, operating temperature range 0 to 50 °C, repetition accuracy max. ±3% of the measuring range, temperature characteristic max. ±2% of the measuring range. (0 to 50 °C, based on 25 °C), current consumption max. 150 mA, measuring principle thermistor (heating element), operating display 3-digit, 7-segment LED (illuminates at output signal ON OUT1: Green
OUT2: Red), operating pressure range 0.1 to 1.5 MPa, switch output PNP open collector 1 output and 1 analogue output (1 to 5 V), with function to switch over the display unit, supply voltage 24 V DC, protection class IP 65, connection cable not included, connection size G 1 1/2

货品

名称	接口螺纹	输出信号	调节单元 [最小] (L/min)	测量范围	最小运行压力 (MPa)	额定电压/电流种类	电流消耗 max. (mA)	重复精度
K- 07 50 00 28	G 1	PNP + Analog output (1-5V)	5,00	150 bis 3000 l/min	1,50	24 VDC	150	max. ±3 % from scale
K- 07 50 00 29	G 1	PNP + Analog output (4-20mA)	5,00	150 bis 3000 l/min	1,50	-	150	max. ±3 % from scale
K- 07 50 00 31	G 1 1/2	PNP + Analog output (1-5V)	10,00	300 bis 6000 l/min	1,50	24 VDC	150	max. ±3 % from scale
K- 07 50 00 32	G 1 1/2	PNP + Analog output (4-20mA)	10,00	300 bis 6000 l/min	1,50	-	150	max. ±3 % from scale
K- 07 50 00 36	G 2	PNP + Analog output (1-5V)	10,00	600 bis 12000 l/min	1,50	24 VDC	150	max. ±3 % from scale
K- 07 50 00 37	G 2	PNP + Analog output (4-20mA)	10,00	600 bis 12000 l/min	1,50	-	150	max. ±3 % from scale

尽管经过了仔细审阅,但我们无法完全排除发生错误的可能,对所提供的信息数据本公司不承担任何责任。