

K-DRUCKVERST MANO VBA

Booster Regulator, pressure gauge, VBA

HANSA FLEX

属性

规格 with pressure gauge

最小运行压力 0.20 MPa

气动压力计接口 Rc 1/8


气动压力计接口数量 2

最大入口压力 0,1 to 1,0 MPa

介质温度 +2 °C to +50 °C

环境温度 +2 °C bis +50 °C

适用介质 压缩空气



描述

Booster regulator, series VBA, increases pressure only where the force is inadequate because of a low network pressure (energy saving measure), no electricity supply necessary, longer service life: doubled compared to conventional model, lower operating noise level: 13 dB (A), improved operational reliability from inbuilt mesh filter on (IN connection) compressed air inlet, reduced condensation levels: air exhaust channels integrated directly into the cylinder tube, suitable for: compressed air, size 1/4, with pressure gauge and silencer, elbow, pneumatic connection: G 1/4, pneumatic connection pressure gauge: G 1/8, pneumatic connections pressure gauge: 2, flow rate 230 l/min, pressure boost 1:2, manually actuated pressure adjustment mechanism, test pressure: 3 MPa, max. operating pressure: 2 MPa, min. operating pressure: 0.2 MPa, media temperature: +2 to +50 °C, ambient temperature: +2 to +50 °C

货品

| 名称 | 气动接口 | 结构尺寸 | 压力调节机械机构 | 压力放大比例 | 流量 (L/min) | 最大工作压力 (MPa) | 试验压力 (MPa) |
|----------------|-------|------|-------------------|--------|---------------|-----------------|---------------|
| K- 07 60 00 02 | G 1/4 | 1/4 | manually operated | 1:2 | 230 | 2,00 | 3,00 |
| K- 07 60 00 09 | G 3/8 | 3/8 | manually operated | 1:2 | 1000 | 1,50 | 1,50 |