# K-KOMPAKTZYL SCHWENKTISCH MSQ

Rotary actuator for compact cylinder MSQ

HANSA-FLEX

## 属性

| | |
|---|---|
| **最大工作压力** | 0,7 MPa |
| **最小运行压力** | 0.10 MPa |
| **规格** | rack and pinion |
| **介质温度** | 0 °C to +60 °C |
| **环境温度** | 0 °C to +60 °C |
| **转动角度** | 0 to 190° |
| **适用介质** | 压缩空气 |
| **系列** | MSQ |
| **更多注明信息** | narrow pivot table unit with low overall height<br>the rotation angle can be adjusted continuously<br>Positioning the housing allow for quick installation<br>the load can be mounted directly on the pivot table<br>\nAir connections of 2 pages possible |



## 货品

| 名称 | 活塞直径 Ø (mm) | 气动接口 | 结构尺寸 | 缓冲 | 每米重量 (kg) |
|---|---|---|---|---|---|
| **K- 07 55 01 13** | 6 | M 3 | 1 | without, with adjustment bolt | 0,075 |
| **K- 07 55 01 18** | 8 | M 5 | 2 | without, with adjustment bolt | 0,105 |
| **K- 07 55 01 21** | 10 | M 5 | 3 | elastic, with adjustment bolt | 0,150 |
| **K- 07 55 01 26** | 12 | M 5 | 7 | elastic, with adjustment bolt | 0,250 |
| **K- 07 55 01 11** | 15 | M 5 | 10 | elastic, with adjustment bolt | 0,530 |
| **K- 07 55 01 16** | 18 | M 5 | 20 | elastic, with adjustment bolt | 0,990 |
| **K- 07 55 01 19** | 21 | G 1/8 | 30 | elastic, with adjustment bolt | 1,290 |
| **K- 07 55 01 22** | 25 | G 1/8 | 50 | elastic, with adjustment bolt | 2,080 |
| **K- 07 55 01 24** | 28 | G 1/8 | 70 | elastic, with adjustment bolt | 2,880 |
| **K- 07 55 01 09** | 32 | G 1/8 | 100 | elastic, with adjustment bolt | 4,090 |
| **K- 07 55 01 14** | 40 | G 1/8 | 200 | elastic, with adjustment bolt | 7,580 |
| **K- 07 55 01 12** | 15 | M 5 | 10 | elastic, with integrated shock absorber | 0,540 |
| **K- 07 55 01 17** | 18 | M 5 | 20 | elastic, with integrated shock absorber | 0,990 |
| **K- 07 55 01 20** | 21 | G 1/8 | 30 | elastic, with integrated shock absorber | 1,290 |
| **K- 07 55 01 23** | 25 | G 1/8 | 50 | elastic, with integrated shock absorber | 2,100 |
| **K- 07 55 01 25** | 28 | G 1/8 | 70 | elastic, with integrated shock absorber | 2,880 |
| **K- 07 55 01 10** | 32 | G 1/8 | 100 | elastic, with integrated shock absorber | 4,100 |
| **K- 07 55 01 15** | 40 | G 1/8 | 200 | elastic, with integrated shock absorber | 7,650 |

*尽管经过了仔细审阅,但我们无法完全排除发生错误的可能,对所提供的信息数据本公司不承担任何责任。*