

# K-STOSSDAEMPFER RB

Shock absorber RB

**HANSA FLEX**

## 属性

系列 RB

更多注明信息 high power density through hydraulic function principle results in min.. size  
Impact speed up to max. 5 m / sec.  
Annular surface at the front side can be used as a mechanical stop



## 描述

Shock absorber, series RB, high power density from hydraulic design principle results in min. dimensions, impact speed up to max. 5 m/sec., the annulus on the end can be used as a mechanical stop, basic version, thread M 8 x 1, stroke 6 mm

## 货品

| 名称             | 行程<br>(mm) | 规格          | 定义             | 螺纹         |
|----------------|------------|-------------|----------------|------------|
| K- 07 55 02 24 | 5          | basic model | Shock absorber | M 8 x 1    |
| K- 07 55 02 25 | 6          | basic model | Shock absorber | M 8 x 1    |
| K- 07 55 02 27 | 6          | basic model | Shock absorber | M 10 x 1   |
| K- 07 55 02 28 | 7          | basic model | Shock absorber | M 10 x 1   |
| K- 07 55 02 30 | 11         | basic model | Shock absorber | M 14 x 1.5 |
| K- 07 55 02 31 | 12         | basic model | Shock absorber | M 14 x 1.5 |
| K- 07 55 02 33 | 15         | basic model | Shock absorber | M 20 x 1.5 |
| K- 07 55 02 35 | 25         | basic model | Shock absorber | M 27 x 1.5 |