# K-STOSSDAEMPFER RB

Shock absorber RB

## 属性

| | |
|---|---|
| **系列** | RB |
| **更多注明信息** | high power density through hydraulic function principle results in min.. size<br>Impact speed up to max. 5 m / sec.<br>Annular surface at the front side can be used as a mechanical stop |



## 描述

Shock absorber, series RB, high power density from hydraulic design principle results in min. dimensions, impact speed up to max. 5 m/sec., the annulus on the end can be used as a mechanical stop, basic version, thread M 8 x 1, stroke 6 mm

## 货品

| 名称 | 行程 (mm) | 规格 | 定义 | 螺纹 |
|---|---|---|---|---|
| **K- 07 55 02 24** | 5 | basic model | Shock absorber | M 8 x 1 |
| **K- 07 55 02 25** | 6 | basic model | Shock absorber | M 8 x 1 |
| **K- 07 55 02 27** | 6 | basic model | Shock absorber | M 10 x 1 |
| **K- 07 55 02 28** | 7 | basic model | Shock absorber | M 10 x 1 |
| **K- 07 55 02 30** | 11 | basic model | Shock absorber | M 14 x 1.5 |
| **K- 07 55 02 31** | 12 | basic model | Shock absorber | M 14 x 1.5 |
| **K- 07 55 02 33** | 15 | basic model | Shock absorber | M 20 x 1.5 |
| **K- 07 55 02 35** | 25 | basic model | Shock absorber | M 27 x 1.5 |

*尽管经过了仔细审阅,但我们无法完全排除发生错误的可能,对所提供的信息数据本公司不承担任何责任。*