


K-SV 6 4 HOSTA

Bulkhead connectors Hosta

HANSA FLEX

属性

| | |
|------|--|
| 工作压力 | Max. 16 bar (at +20 °C) |
| 工作温度 | -20 °C to +70 °C |
| 原料 | 黄铜镀镍 |
| 紧压环 | Hostaform (black nickel-plated for Ø 10, 12) |
| O 形圈 | NBR, siliconefree |
| 夹钳 | Stainless steel AISI 316 |



提示

其它数据应客户要求提供。

描述

Economy yet very high-quality series of push-in fittings made of nickel-plated brass. Compact, space-saving, lightweight design. An O-ring in the fillet at the end of the thread guarantees a tight connection for all male thread parts, even on rough surfaces.

货品

| 名称 | 螺纹 | 用于软管外径-Ø | L1 (mm) | SW |
|----------------|----------|----------|------------|-------|
| K- 07 40 29 57 | M 10 x 1 | 4 mm | 32,0 | 13 mm |
| K- 07 40 29 58 | M 14 x 1 | 6 mm | 33,5 | 17 mm |
| K- 07 40 29 59 | M 16 x 1 | 8 mm | 37,0 | 18 mm |
| K- 07 40 29 60 | M 17 x 1 | 10 mm | 39,5 | 20 mm |
| K- 07 40 29 61 | M 20 x 1 | 12 mm | 42,0 | 24 mm |