

K-XV AG R

Double nipples, conical male thread

HANSA FLEX

属性

| | |
|------|---------------------------------|
| 工作压力 | 10 bar |
| 介质温度 | max. +90 °C |
| 环境温度 | Max. +90 °C |
| 原料 | Brass with a bare metal surface |



提示

The dimensions of the standard screw fittings may change slightly during the life of the catalogue as a result of optimisation processes. 其它数据应客户要求提供。

附加信息

Further types and dimensions on request.

货品

| 名称 | 螺纹 1 | 螺纹 2 | L1 (mm) | L2 (mm) | L3 (mm) | SW |
|----------------|-------|-------|------------|------------|------------|-------|
| K- 07 40 44 60 | R 1/8 | R 1/8 | 21,0 | 8,0 | 8,0 | 10 mm |
| K- 07 40 44 61 | R 1/8 | R 1/4 | 24,5 | 8,0 | 11,5 | 14 mm |
| K- 07 40 44 62 | R 1/8 | R 3/8 | 26,0 | 8,0 | 13,0 | 17 mm |
| K- 07 40 00 26 | R 1/4 | R 1/4 | 30,0 | 12,0 | 12,0 | 14 mm |
| K- 07 40 44 66 | R 1/4 | R 3/8 | 29,5 | 11,5 | 13,0 | 17 mm |
| K- 07 40 44 67 | R 1/4 | R 1/2 | 32,5 | 11,5 | 15,5 | 22 mm |
| K- 07 40 00 27 | R 3/8 | R 3/8 | 38,0 | 16,0 | 16,0 | 22 mm |
| K- 07 40 44 70 | R 3/8 | R 1/2 | 34,0 | 15,5 | 13,0 | 22 mm |
| K- 07 40 44 71 | R 3/8 | R 3/4 | 36,5 | 13,0 | 17,5 | 27 mm |
| K- 07 40 00 28 | R 1/2 | R 1/2 | 38,0 | 16,0 | 16,0 | 27 mm |
| K- 07 40 44 74 | R 1/2 | R 3/4 | 39,0 | 17,5 | 15,5 | 27 mm |
| K- 07 40 44 75 | R 1/2 | R 1 | 42,5 | 20,0 | 15,5 | 34 mm |
| K- 07 40 00 29 | R 3/4 | R 3/4 | 51,5 | 22,0 | 22,0 | 32 mm |
| K- 07 40 44 78 | R 3/4 | R 1 | 44,5 | 20,0 | 17,5 | 34 mm |
| K- 07 40 00 30 | R 1 | R 1 | 47,0 | 19,5 | 19,5 | 41 mm |