


属性

接口 1	米制螺母螺纹
密封形式 1	带O形圈的24°外锥
缩略词	DKOS
标准	ISO 8434-1
供货范围	压力内接头 + 压力卡套
原料	钢
表面保护	电镀涂层



货品

名称	DN	尺寸	英寸	G1	用于管外径-Ø (mm)	S1	OR
PAY 506 AOS 03	6	4	1/4"	M 14 x 1.5	6	17	4.0 x 1.5
PAY 506 AOS 04	6	4	1/4"	M 16 x 1.5	8	19	6.0 x 1.5
PAY 506 AOS	6	4	1/4"	M 18 x 1.5	10	22	7.5 x 1.5
PAY 508 AOS	8	5	5/16"	M 20 x 1.5	12	24	9.0 x 1.5
PAY 510 AOS 08	10	6	3/8"	M 20 x 1.5	12	24	9.0 x 1.5
PAY 510 AOS	10	6	3/8"	M 22 x 1.5	14	27	12.0 x 2.0
PAY 513 AOS	12	8	1/2"	M 24 x 1.5	16	30	12.0 x 2.0
PAY 516 AOS	16	10	5/8"	M 30 x 2	20	36	16.0 x 2.5
PAY 520 AOS	19	12	3/4"	M 36 x 2	25	46	20.0 x 2.5
PAY 525 AOS	25	16	1"	M 42 x 2	30	50	25.0 x 2.5