LKM IR ST DK
带保险的插式接合器接头(空气)

HANSA-FLEX

属性

结构类型	快速闭锁接合器接头
接口 1	BSP内螺纹,圆柱形
接口 2	
工作压力	最大12巴
空气流量	1.800 l/min (at 6 bar and Δp = 1 bar)
介质温度	-20 °C to +70 °C
壳体	Aluminium, anodised
螺纹	Nickel-plated brass
内部部件	Stainless steel
钮,阀	Hardened, galvanised steel
密封材料	NBR



提示

Not suitable for hitting / pulsating tools.
其它数据应客户要求提供。

描述

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414.

货品

名称	接口螺纹	接口	长度 (mm)	SW (mm)
LKM 06 IR ST DK	1/4” 螺纹 -19	G 1/4 female	71,5	21
LKM 10 IR ST DK	G 3/8" -19	G 3/8 female	75,5	21
LKM 13 IR ST DK	G 1/2" -14	G 1/2 female	77,5	24

尽管经过了仔细审阅,但我们无法完全排除发生错误的可能,对所提供的信息数据本公司不承担任何责任。