LKM MM ST DK

带保险的插式接合器接头(空气)



属性	
结构类型	快速闭锁接合器接头
接口1	软管接口
接口 2	
工作压力	最大12巴
空气流量	1.800 l/min (at 6 bar and Δp = 1 bar)
介质温度	-20 °C to +70 °C
売体	Aluminium, anodised
螺纹	Nickel-plated brass
内部部件	Stainless steel
钮,阀	Hardened, galvanised steel
密封材料	NBR



提示

Not suitable for hitting / pulsating tools.

其它数据应客户要求提供。

描述

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414.

货品					
名称	用于软管-ID (mm)	接口	长度 (mm)	SW (mm)	
LKM 06 MM ST DK	6	Stem, I.D. 6	88,5	21	
LKM 09 MM ST DK	9	Stem, I.D. 9	88,5	21	
LKM 13 MM ST DK	13	Stem, I.D. 13	88,5	21	