

属性

原料	钢
应用范围	针对摆动的软管的人员保护。
温度范围	-30°C 至 +150°C
许可	BGR 237 DIN EN ISO 4413 BGI 5100 机械指令 2006/42/EG



货品

名称	用于机器固定点直径	用于软管 DN	用于软管外径-Ø	最大工作压力 (bar)
STOP LOCK 45 85	11.5-15.5mm	02 - 04	4.5-8.5mm	630
STOP LOCK 1119	12-20mm	05 - 08	11-19mm	450
STOP LOCK 1119 UHP	12-20mm	06	11-19mm	700
STOP LOCK 1728	18-24mm	10 - 12	17-28mm	450
STOP LOCK 2331	22-30mm	16	23-31mm	420
STOP LOCK 2635	28-36mm	19	26-35mm	420
STOP LOCK 3444	32-42mm	25	34-44mm	420
STOP LOCK 4352	38-52mm	31	43-52mm	210
STOP LOCK 5061	44-52mm	38	50-61mm	200
STOP LOCK 6074	56-62mm	51	60-74mm	185
STOP LOCK 4352 HP	38-52mm	31	43-52mm	350
STOP LOCK 5061 HP	44-52mm	38	50-61mm	310
STOP LOCK 6074 HP	56-62mm	51	60-74mm	270
STOP LOCK 4352 UHP	38-52mm	31	43-52mm	500
STOP LOCK 5061 UHP	44-52mm	38	50-61mm	450
STOP LOCK 6074 UHP	56-62mm	51	60-74mm	420

附件

STOP LOCK-KIT	软管压紧式固定装置工具套件
STOP LOCK-TAPE	软管压紧式固定带